

Copyright, 1997, Minnesota Mining and Manufacturing Company.
All rights reserved. Copying and/or downloading of this information for
the purpose of properly utilizing 3M products is allowed provided that:
1) the information is copied in full with no changes unless prior agreement

- is obtained from 3M, and
 2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

DIVISION: DENTAL PRODUCTS

TRADE NAME:

1980 AND 1958 SERIES SOF-LEX CONTOURING AND POLISHING DISCS

ID NUMBER/U.P.C.:	41-5300-5264-0 70-2004-2154-6 70-2004-4244-3 70-2004-8096-3 70-2004-8105-2 70-2004-8107-8 70-2010-1690-7 70-2010-1694-9 70-2010-1696-4 70-2010-1698-0	+H-444 +H-444 +H-444 +H-444	- 10-827 10-842 11-253 11-255 11-261 - - -	32-0 3%-0 31-0 3+-0	70-2004-2153-8 70-2004-2155-3 70-2004-7412-3 70-2004-8097-1 70-2004-8106-0 70-2004-8108-6 70-2010-1691-5 70-2010-1695-6 70-2010-1697-2	+H-444 +H-444 +H-444 +H-444	110-826 110-828 111-201 111-254 111-256 111-264 - - -	36-0 3Z-0 30-0 32-0 3%-0
	\U-\U\U\U-1698-U	_	_	_				

ISSUED: JANUARY 2, 1997 SUPERSEDES: DECEMBER 16, 1996

DOCUMENT: 11-2635-8

1. INGREDIENT	C.A.S. NO.	PERCENT	
CURED URETHANE BACKING	None	40.0 - 22.0 - 15.0 -	31.0

2. PHYSICAL DATA

BOILING POINT:	N/A
VAPOR PRESSURE:	N/A
VAPOR DENSITY:	N/A
EVAPORATION RATE:	N/A
SOLUBILITY IN WATER:	N/A
SP. GRAVITY:	N/D
PERCENT VOLATILE:	N/A
pH:	N/A
VISCOSITY:	N/A
MELTING POINT	N/D

MELTING POINT.... solid abrasives discs: 5/8", 1/2", 3/8" in diameter., color: APPEARANCE AND ODOR:

light gray to dark brown and light blue to black.

3. FIRE AND EXPLOSION HAZARD DATA

..... 451.00 F FLASH POINT:...



MSDS: 1980 AND 1958 SERIES SOF-LEX CONTOURING AND POLISHING DISCS JANUARY 2, 1997

PAGE: 2 of 4

3. FIRE AND EXPLOSION HAZARD DATA (continued)

FLAMMABLE LIMITS - UEL: N/A
AUTOIGNITION TEMPERATURE: ... N/D
EXTINGUISHING MEDIA:
Water, Carbon dioxide, Dry chemical, Foam
SPECIAL FIRE FIGHTING PROCEDURES:
None known.
UNUSUAL FIRE AND EXPLOSION HAZARDS:
None known.
NFPA HAZARD CODES: HEALTH: 0 FIRE: 0 REACTIVITY: 0
UNUSUAL REACTION HAZARD: none
OSHA FIRE HAZARD CLASS: Not applicable

4. REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY - MATERIALS TO AVOID:
None known.
HAZARDOUS POLYMERIZATION: Will Not Occur
HAZARDOUS DECOMPOSITION PRODUCTS:
None known.

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE: Not applicable.

RECOMMENDED DISPOSAL:

Dispose of waste product in a sanitary landfill.

ENVIRONMENTAL DATA:

No data available.

REGULATORY INFORMATION:

Volatile Organic Compounds: N/A. VOC Less H2O & Exempt Solvents: N/D.

EPCRA HAZARD CLASS:

FIRE HAZARD: No PRESSURE: No REACTIVITY: No ACUTE: No CHRONIC: No

6. SUGGESTED FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

Flush skin with large amounts of water. If irritation persists, get medical attention.

INHALATION:

No need for first aid is anticipated.



MSDS: 1980 AND 1958 SERIES SOF-LEX CONTOURING AND POLISHING DISCS JANUARY 2, 1997

PAGE: 3 of 4

6. SUGGESTED FIRST AID

(continued)

IF SWALLOWED:

No need for first aid is anticipated.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

Avoid eye contact.

SKIN PROTECTION:

Avoid skin contact.

VENTILATION PROTECTION:

Not applicable.

RESPIRATORY PROTECTION:

Not applicable.

PREVENTION OF ACCIDENTAL INGESTION:

Not applicable.

RECOMMENDED STORAGE:

Not applicable.

FIRE AND EXPLOSION AVOIDANCE:

Not applicable.

EXPOSURE LIMITS

INGREDIENTS	VALUE	UNIT	TYPE AUTH	SKIN*
CURED URETHANE BACKING	NONE	NONE	NONE NONE	
PAPER	NONE	NONE	NONE NONE	
ALUMINUM OXIDE GRIT AND BINDER	NONE	NONE	NONE NONE	

* SKIN NOTATION: Listed substances indicated with "Y" under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

Mechanical eye irritation: signs/symptoms can include irritation, redness, scratching of the cornea and tearing.



MSDS: 1980 AND 1958 SERIES SOF-LEX CONTOURING AND POLISHING DISCS JANUARY 2, 1997

PAGE: 4 of 4

8. HEALTH HAZARD DATA

(continued)

Dust created by cutting, grinding, sanding, or machining may cause eye irritation.

SKIN CONTACT:

Mechanical skin irritation: signs/symptoms can include itching and redness.

INHALATION:

No adverse health effects are expected from inhalation exposure.

This product may have a characteristic odor; however, no adverse health effects are anticipated.

IF SWALLOWED:

Ingestion is not a likely route of exposure to this product.

SECTION CHANGE DATES

HEADING

SECTION CHANGED SINCE DECEMBER 16, 1996 ISSUE

Abbreviations: N/D - Not Determined N/A - Not Applicable

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.